

Specim FX10 FOV12 lens specifications

1. Technical specifications

1.1. General information

Spectral camera	Specim FX10
Wavelength range (μm)	0.4 - 1.0
Product code	06FOB00200

1.2. Specifications with spectral camera

PARAMETER	VALUE	COMMENT	
Nominal working distance (mm)	1000	Working distance used for all specifications	
Field of view (deg)	11	Nominal value	
Entrance pupil position (mm)	19.6	From the first lens surface	
Working distance (mm)	366 - ∞	Distance from the object to the first lens surface	
Minimum object length (mm)	67	Object length at minimum working distance	
Adjustable focus	Yes	Focus can be adjusted and locked	
Filter thread	M30.5 x 0.5		
Lens mount	C-mount	Adapter to custom mount required (Product No 0106193)	
Resolution (pix)	3.4	Average over all field points and wavelengths	
MTF (%) at 30 lp/mm	35		
Maximum distortion (%)	-0.7		
Minimum relative illumination (%)	92		

1.3. Specifications for lens only (A) and lens with spectral camera (B)

PARAMETER	Α	В	COMMENT
Image width (mm)	10.2	8.2	
Effective focal length (mm)	50.4	40.4	At infinite working distance; tolerance ± 1%
Working F-number	3.1 - closed	2.5 - closed	
Average transmission (%)	89	-	
Dimensions (mm)	34 x 53	- Diameter x Length	

All specification values given above are valid at the nominal working distance if not stated otherwise.



2. Figures




Figure 1. MTF averaged over wavelengths as a function of frequency.




Figure 2. MTF averaged over wavelengths as a function of normalized field.




Figure 3. Full width at half maximum of the spatial spot as a fuction of wavelength.




Figure 4. Relative distortion as a function of normalized field. $\label{eq:figure} % \begin{center} \begin{ce$




Figure 5. Relative illumination as a function of normalized field.




Figure 6. Transmission as a function of wavelength (lens only). Measured data is scaled with respect to the F-numbers ratio.

All specification values given above are valid at the nominal working distance if not stated otherwise.



3. Object dimensions and depth of field at different working distances

NOMINAL OBJECT DIMENSIONS

WORKING DISTANCE (CM)	ACROSS TRACK / LENGTH (MM)	ALONG TRACK / WIDTH (MM)	DEPTH OF FIELD (MM)
37	67	0.3	4
40	74	0.3	4
50	95	0.4	7
60	115	0.5	10
70	135	0.6	13
80	155	0.7	17
90	176	0.8	21
100	196	0.8	26
150	297	1.3	57
200	399	1.7	100
300	602	2.5	230
500	1010	4.2	620